



TT SILENT M

PRODUCT SPECIFICATIONS

TECHNICAL DATA

INLINE MIXED FLOW FANS

PERFORMANCE

Model	Speed	RPM*	Sones	Duct Dia	Watts*	Amps*	CFM vs. Static Pressure (Ps) in WG											Volts/Hz
							0"	0.1"	0.2"	0.3"	0.4"	0.5"	0.6"	0.7"	0.8"	0.9"	1.0"	
TT Silent M 100	high	2363	1.2	4"	28	0.24	128	113	97	76	56	32	10	-	-	-	-	120/60
	low	2065	0.3		22	0.2	99	81	62	40	12	-	-	-	-	-	-	-
TT Silent M 125	high	2303	0.9	5"	35	0.3	188	174	158	130	94	60	30	0	-	-	-	120/60
	low	1990	0.4		23	0.22	116	90	68	38	0	-	-	-	-	-	-	-
TT Silent M 150	high	2570	2.0	6"	67	0.55	327	314	299	284	266	245	224	190	140	89	48	120/60
	low	1847	1.0		53	0.45	240	220	192	171	135	111	86	56	28	5	-	-
TT Silent M 200	high	2303	2.0	8"	111	0.93	473	455	432	405	379	352	313	274	221	155	89	120/60
	low	1990	0.7		70	0.58	349	323	294	249	203	158	108	57	26	13	0	0
TT Silent M 250	high	2570	4.0	10"	200	1.68	880	874	866	858	850	842	832	821	794	751	708	120/60
	low	1847	2.0		130	1.11	655	648	630	608	587	565	531	497	450	390	330	330
TT Silent M 315	high	2570	3.5	12 3/8"	353	2.95	1050	1026	999	971	942	914	884	853	823	794	764	120/60
	low	1847	2.0		236	1.95	830	804	770	726	682	638	581	524	464	399	335	335

MODEL	QUANTITY	COMMENTS	PROJECT
			location:
			architect:
			engineer:
			contractor:
			submitted by:

Tel: 888-640-0925 Sales@ventsus.com
 513-348-3853 VentsUS.com
 Fax: 513-268-4597 11013 Kenwood Road,
 Cincinnati, Ohio 45242

