




AIRLITE ERV EC


Energy recovery ventilators for commercial applications featuring advanced EC (Electronically Commutated) motor technology.






ERV 5 EC
ERV 8 EC
ERV 13 EC
ERV 17 EC
ERV 25 EC

AIRLITE energy recovery ventilators are available in five sizes with one, two or three high-efficiency EC fans in array on both supply and exhaust sides. Units are specially designed for commercial applications.



ERV 5 EC, ERV 8 EC



CASING

Steel casing is covered with high quality multilayer aluminium and zinc alloy to prevent corrosion. The casing is equipped with a switch to turn the ventilator off when the service panel is opened. Service access from both left and right side. For outdoor installation the roof is necessary (optional).

ENERGY RECOVERY CORE

Unique enthalpy heat exchanger provides high-efficient heat & humidity recovery. No drain pan required.

FANS

The unit is equipped with supply and exhaust centrifugal fans featuring backward-curved blades and advanced EC (Electronically Commutated) motor technology. These fans deliver superior energy efficiency and precise speed control. They come with built-in thermal overheating protection and an automatic restart function, ensuring consistent and reliable performance. Additionally, both the electric motors and impellers are dynamically balanced to minimise noise and vibration, providing smooth and efficient operation.

DEFROST SYSTEM

Fan stop defrost system is activated when the outdoor temperature falls below 23° F (-5° C).


FILTER

Washable MERV 6 air filters in exhaust and supply air streams. Filters MERV 8, MERV 13 optional.


CONTROL

The unit incorporates an integrated automation and control system with following functions:

- Operation mode switch.
- Airflow balancing by supply and exhaust fan independent speed adjustment.
- Automatic recovery core frost protection.
- External control device connection.



ERV 13 EC, ERV 17 EC









ERV 25 EC



TECHNICAL DATA





Parameters	AIRLITE ERV 5 EC	AIRLITE ERV 8 EC	AIRLITE ERV 13 EC
Voltage [V / 60 Hz]	1 ~ 208	1 ~ 208	1 ~ 208
Unit power [W]	330	480	650
Unit current [A]	2.4	3.4	4.5
Minimum circuit Amps [MCA]	3.0	4.3	5.7
Maximum over current protection [MOP]	3.9	5.6	6.0
Sensible effectiveness @ max airflow [%]	63	65	63
Air flow @ ESP 0.4" WG [cfm]	400	580	730
Air flow max [cfm]	490	650	800
Transported air temperature [F]	-35 up to +140	-35 up to +140	-35 up to +140
Outer skin casing material	21 gauge galvanized steel	21 gauge galvanized steel	21 gauge galvanized steel
Insulation	1" mineral wool	1" mineral wool	1" mineral wool
Connected air duct size [in]	8x14	8x14	8x20



- Sensible winter & summer
- Winter total
- Summer total

TECHNICAL DATA

Parameters	AIRLITE ERV 17 EC	AIRLITE ERV 25 EC
Voltage [V / 60 Hz]	1 ~ 208	1 ~ 208
Unit power [W]	940	1385
Unit current [A]	10.5	13.4
Minimum circuit Amps [MCA]	13.2	16.8
Maximum over current protection [MOP]	13.8	16.2
Sensible effectiveness @ max airflow [%]	58	55
Air flow @ ESP 0.4" WG [cfm]	1140	1600
Air flow max [cfm]	1280	1800
Transported air temperature [F]	-35 up to +140	-35 up to +140
Outer skin casing material	21 gauge galvanized steel	21 gauge galvanized steel
Insulation	1" mineral wool	1" mineral wool
Connected air duct size [in]	8x20	8x30



— Sensible winter & summer
 — Winter total
 — Summer total



VENTS-US reserves the rights to modify any of its products' features, designs, components and specifications at any time and without notice to maintain the development and quality of manufactured goods.

Vents-US.com
 07 | 2024

Tel: 888-640-0925
 Fax: 513-268-4597
 Sales@vents-us.com
 Vents-US.com
 400 Murray Road, Cincinnati,
 OH 45217