

# AirVENTS CFH 9000

Double-deck commercial heat recovery air handling units for floor mounting with high-efficient counter-flow heat exchanger. Available in 8 standard sizes



- Sound pressure level LpA at 3 m: 48
- Sound pressure level LpA at 3 m: 48
- Heat exchanger type: Counter flow
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel

	Unit of measurement	AirVENTS CFH 9000
Phases	-	3
Minimum supply voltage	V	380
Maximum supply voltage	V	480
Power supply frequency	Hz	50/60
Unit current	A	8.5
Maximum performance @0.1"	CFM	5298
Sound pressure level LpA at 3 m	dB(A)	48
Sound pressure level LpA at 3 m	dB(A)	48
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Aluminum
Extract filter	-	MERV13 (MERV8)
Supply filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

## Dimensions

L	W	H	H1	S1
117.72"	90.94"	67.32"	23.62"	47.24"

