

AirVENTS CFP 1200

Ceiling-mounted commercial heat recovery air handling units with high-efficient counter-flow heat exchanger. Available in 8 standard sizes

- Sound pressure level LpA at 3 m: 39
- Sound pressure level LpA at 3 m: 39
- Heat exchanger type: Counter flow
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel



| | Unit of measurement | AirVENTS CFP 1200 |
|--|---------------------|-------------------|
| Speed | - | 1 |
| Phases | - | 1 |
| Minimum supply voltage | V | 200 |
| Maximum supply voltage | V | 240 |
| Power supply frequency | Hz | 50/60 |
| Unit current | A | 5.3 |
| Maximum performance @0.1" | CFM | 706 |
| Sound pressure level LpA at 3 m | dB(A) | 39 |
| Sound pressure level LpA at 3 m | dB(A) | 39 |
| Heat exchanger type | - | Counter flow |
| Heat exchanger material | - | Aluminum |
| Extract filter | - | MERV13 (MERV8) |
| Supply filter | - | MERV13 (MERV8) |
| Transported air temperature (max) | °C | 122 |
| Transported air temperature (min) | °C | -31 |
| Ingress protection rating | - | IP34 |
| Ingress protection rating of the drive | - | IP54 |

Dimensions

| L | W | H | H1 | S1 |
|--------|--------|--------|-------|--------|
| 70.87" | 56.69" | 14.96" | 9.84" | 19.69" |

