

AirVENTS CFP 1200

Ceiling-mounted commercial heat recovery air handling units with high-efficient counter-flow heat exchanger. Available in 8 standard sizes

- Sound pressure level LpA at 3 m: 39
- Sound pressure level LpA at 3 m: 39
- Heat exchanger type: Counter flow
- Heat exchanger material: Aluminum
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound-insulated casing
- Casing material: Aluzinc steel



	Unit of measurement	AirVENTS CFP 1200
Phases	-	1
Minimum supply voltage	V	200
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Unit current	A	5.3
Maximum airflow	CFM	706
Sound pressure level LpA at 3 m	dB(A)	39
Sound pressure level LpA at 3 m	dB(A)	39
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Aluminum
Extract filter	-	MERV13 (MERV8)
Supply filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

Dimensions

L	W	H	H1	S1
70.87"	56.69"	14.96"	9.84"	19.69"

