

AirVENTS CFP 6000

Ceiling-mounted commercial heat recovery air handling units with high-efficient counter-flow heat exchanger. Available in 8 standard sizes

- Sound pressure level LpA at 3 m: 40
- Sound pressure level LpA at 3 m: 40
- Heat exchanger type: Counter flow
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel



	Unit of measurement	AirVENTS CFP 6000
Speed	-	1
Phases	-	3
Minimum supply voltage	V	380
Maximum supply voltage	V	480
Power supply frequency	Hz	50/60
Unit current	A	8.5
Maximum performance @0.1"	CFM	3531
Sound pressure level LpA at 3 m	dB(A)	40
Sound pressure level LpA at 3 m	dB(A)	40
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Aluminum
Extract filter	-	MERV13 (MERV8)
Supply filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

Dimensions

L	W	H	H1	S1
114.17"	74.80"	39.37"	19.69"	31.50"

