

# AirVENTS CFV 1200



Low-footprint commercial heat recovery air handling units, vertical outlets and with high-efficient counter-flow heat exchanger. Available in five standard sizes

- Sound pressure level LpA at 3 m: 36
- Sound pressure level LpA at 3 m: 36
- Heat exchanger type: Counter flow
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound insulation
- Motor type: EC
- Casing material: Aluzinc steel

	Unit of measurement	AirVENTS CFV 1200
Phases	-	1
Minimum supply voltage	V	200
Maximum supply voltage	V	240
Power supply frequency	Hz	50/60
Unit current	A	5.3
Maximum performance @0.1"	CFM	705
Sound pressure level LpA at 3 m	dB(A)	36
Sound pressure level LpA at 3 m	dB(A)	36
Heat exchanger type	-	Counter flow
Heat exchanger material	-	Aluminum
Extract filter	-	MERV13 (MERV8)
Supply filter	-	MERV13 (MERV8)
Transported air temperature (max)	°C	122
Transported air temperature (min)	°C	-31
Ingress protection rating	-	IP34
Ingress protection rating of the drive	-	IP54

## Dimensions

L	W	H	H1
55.12"	31.50"	49.21"	Ø 12.40"

