

# AirVENTS RV 1500



Low-footprint commercial heat recovery air handling units with vertical outlets. Available in 7 standard sizes

- Sound pressure level LpA at 3 m: 35
- Heat exchanger type: Rotary
- Extract filter: MERV13 (MERV8)
- Supply filter: MERV13 (MERV8)
- Sound insulation
- Motor type: EC

|  | Unit of measurement | AirVENTS RV 1500 |
|--|---------------------|------------------|
| Phases                                 | -                   | 1                |
| Minimum supply voltage                 | V                   | 200              |
| Maximum supply voltage                 | V                   | 240              |
| Power supply frequency                 | Hz                  | 50/60            |
| Unit current                           | A                   | 5.3              |
| Sound pressure level LpA at 3 m        | dB(A)               | 35               |
| Heat exchanger type                    | -                   | Rotary           |
| Heat exchanger material                | -                   | Aluminum         |
| Extract filter                         | -                   | MERV13 (MERV8)   |
| Supply filter                          | -                   | MERV13 (MERV8)   |
| Transported air temperature (max)      | °C                  | 122              |
| Transported air temperature (min)      | °C                  | -31              |
| Ingress protection rating              | -                   | IP34             |
| Ingress protection rating of the drive | -                   | IP54             |

## Dimensions

| L      | W      | H      | H1    | S1     |
|--------|--------|--------|-------|--------|
| 55.12" | 37.80" | 55.12" | 9.84" | 19.69" |

