

TwinFresh Elite 200 Pro L055



HRV unit for single-room ventilation

- Power of electrical preheater: 100
- Filter: MERV 5
- Motor type: EC
- Preheater: Electric
- Control: Remote Control
- Casing material: Plastic
- Humidity sensor
- CO2 sensor
- VOC sensor
- Temperature sensor
- Sound pressure level LpA at 10 ft: 3.4

| | Unit of measurement | TwinFresh Elite 200 Pro L055 | | | |
|-----------------------------------|---------------------|------------------------------|------|-----------------------|--|
| Speed | - | 3 | | | |
| Minimum supply voltage | V | 120 | | | |
| Maximum supply voltage | V | 120 | | | |
| Power supply frequency | Hz | 60 | | | |
| Rated power | W | 5 | 11 | 22 | |
| Power of electrical preheater | W | 100 | | | |
| Maximum unit current | A | 0.9 | 0.95 | 1.05 | |
| Maximum performance @0.1" | CFM | 9 | 30 | 41 (53 in Boost mode) | |
| Heat recovery efficiency | % | | | | |
| Heat recovery efficiency, max | % | 85 | | | |
| Heat exchanger material | - | Copper | | | |
| Filter | - | MERV 5 | | | |
| Ingress protection rating | - | IPX4 | | | |
| Sound pressure level LpA at 3 ft | Sones | 0.8 | 3.9 | 6.6 | |
| Sound pressure level LpA at 10 ft | Sones | 0.4 | 2.0 | 3.4 | |

Dimensions

| ØD | L | L1 |
|-----------------|-------------------|------------------|
| 8 1/8" (206 mm) | 25 9/16" (650 mm) | 21 5/8" (550 mm) |

