

TwinFresh Elite Eco E



Single-room heat recovery ventilation unit with ceramic heat exchanger

- Power of electrical reheater: 160
- Filter: MERV 5 (optional MERV 8)
- Motor type: EC
- Reheater: Electric
- Control: Remote Control
- Casing material: ABS Plastic
- Temperature sensor

	Unit of measurement	TwinFresh Elite Eco E		
Speed	-	3		
Minimum supply voltage	V	120		
Maximum supply voltage	V	120		
Power supply frequency	Hz	60		
Rated power	W	3	5	8
Power of electrical reheater	W	160		
Maximum unit current	A	1.85	1.88	1.91
Air flow in ventilation mode	CFM	6	18	28
Air flow in heat recovery mode	CFM	6	18	28
Heat recovery efficiency	%			
Heat recovery efficiency, max	%	92		
Heat exchanger material	-	Ceramic		
Filter	-	MERV 5 (optional MERV 8)		
Transported air temperature (max)	°C	40		
Transported air temperature (min)	°C	-25		
Ambient air humidity max	%	70		
Ingress protection rating	-	IPX4		
Sound pressure level LpA at 3 ft	Sones			

Sound pressure level LpA at 10 ft	Sones	
-----------------------------------	-------	--

Dimensions

L	L1
21 1/4" (540 mm)	17 3/8" (439 mm)

