


VKVA 225 EC



Aluminum roof fans

- Sound pressure level LpA at 3 m: 47
- Sound pressure level LpA at 3 m: 47
- Motor type: EC
- Impeller type: Centrifugal impeller with backward curved blades
- Casing material: Galvanized steel

	Unit of measurement	VKVA 225 EC
Speed	-	1
Phases	-	1
Minimum supply voltage	V	230
Maximum supply voltage	V	230
Power supply frequency	Hz	60
Rated power	W	
Rated power	W	101
Unit current	A	
Maximum unit current	A	0.8
Maximum airflow	m ³ /h	
Maximum airflow	m ³ /h	
Maximum performance @0.1"	CFM	759
rotation speed at 50hz	-	
rotation speed at 60hz	-	2400
Sound pressure level LpA at 3 m	dB(A)	47
Sound pressure level LpA at 3 m	dB(A)	47
Weight	kg	0
Transported air temperature (max)	°C	60
Transported air temperature (min)	°C	-25
Ingress protection rating	-	IPX4

Ingress protection rating of the drive	-	IP55
--	---	------

Dimensions

Ecodesign

Trademark	Vents
Model	VKVA 225 EC
Type of drive installed	Integrated VSD
Type of heat recovery system	None
Nominal flow rate (m ³ /s)	0.215
Nominal external pressure (Pa)	186
Maximum external leakage rates (%)	2.7
Static efficiency (%)	48.3
Effective electric power input (kW)	0.098
Sound power level (dB(A))	67
Declared typology	NRVU UVU