

VUE 350 VB EC A21



The air-handling units are the fully featured ventilation units with heat recovery for air filtration, fresh air supply and stale air extract. During operation the extract air heat is transferred to the supply air stream by the highly efficient plate heat exchanger

- Motor type: EC
- Enthalpy heat exchanger
- Bypass: Auto
- Reheater: Optional
- Preheater: Optional
- BMS protocol: ModBus
- Control: Smartphone
- Casing material: Coated steel
- Humidity sensor: Optional
- CO2 sensor: Optional
- VOC sensor: Optional
- PM2.5 sensor: Optional

| | Unit of measurement | VUE 350 VB EC A21 |
|-------------------------------|---------------------|-------------------|
| Connected air duct size | in | 6 19/64" |
| Speed | - | 1 |
| Phases | - | 1 |
| Minimum supply voltage | V | 120 |
| Maximum supply voltage | V | 120 |
| Power supply frequency | Hz | 50/60 |
| Rated power | W | 178 |
| Maximum unit current | A | 2.8 |
| Heat recovery efficiency, max | % | 91 |
| Extract filter | - | MERV8 |

Dimensions

| D | B | H | L |
|----------|-----------|-----------|-----------|
| 6 19/64" | 22 61/64" | 26 37/64" | 28 47/64" |

