

## **VUT 350 VB EC A14**



The air-handling units are the fully featured ventilation units with heat recovery for air filtration, fresh air supply and stale air extract. During operation the extract air heat is transferred to the supply air stream by the highly efficient plate heat exchanger

Motor type: EC Bypass: Manual

Control: Remote Control
Casing material: Coated steel
Humidity sensor: Optional
CO2 sensor: Optional
VOC sensor: Optional
PM2.5 sensor: Optional

|                               | Unit of measurement | VUT 350 VB EC A14 |  |
|-------------------------------|---------------------|-------------------|--|
| Connected air duct size       | in                  | 6 19/64"          |  |
| Speed                         | -                   | 1                 |  |
| Phases                        | -                   | 1                 |  |
| Minimum supply voltage        | V                   | 120               |  |
| Maximum supply voltage        | V                   | 120               |  |
| Power supply frequency        | Hz                  | 50/60             |  |
| Rated power                   | W                   | 178               |  |
| Maximum unit current          | А                   | 2.8               |  |
| Heat recovery efficiency, max | %                   | 92                |  |
| Extract filter                | -                   | MERV8             |  |

## **Dimensions**

| D        | В         | Н         | L         |
|----------|-----------|-----------|-----------|
| 6 19/64" | 22 61/64" | 26 37/64" | 28 47/64" |



